

Model			MI-18T3/DHN1-C	MI-22T3/DHN1-C	MI-28T3/DHN1-C	MI-36T3/DHN1-C	MI-45T3/DHN1-C	MI-56T3/DHN1-C	MI-71T3/DHN1-C
Power supply			1-phase,220-240V,50/60Hz						
Capacity	Cooling	kW	1.8	2.2	2.8	3.6	4.5	5.6	7.1
	Heating	kW	2.2	2.6	3.2	4.0	5.0	6.3	8.0
Power input	Cooling	W	23	23	23	30	46	53	53
	Heating	W	23	23	23	30	46	53	53
Airflow rate(H/M/L)		m ³ /h	590/520/415	590/520/415	590/520/415	655/560/465	856/740/600	905/740/580	970/800/660
External static pressure(Min/Std/Max)		Pa	0/10/30	0/10/30	0/10/30	0/10/30	0/10/30	0/10/30	0/10/30
Sound pressure level(H/M/L)		dB(A)	34/26/24	34/26/24	34/26/24	37/31/28	38/31/28	38/31/28	40/32/29
Sound power level(H/M/L)		dB(A)	45/38/37	45/38/37	45/38/37	48/43/41	49/43/41	49/43/41	51/44/42
Net dimension(W×H×D)		mm	740×210×470	740×210×470	740×210×470	740×210×470	960×210×470	960×210×470	1180×210×470
Packing dimension(W×H×D)		mm	910×230×510	910×230×510	910×230×510	910×230×510	1130×230×510	1130×230×510	1350×230×510
Net/gross weight		kg	13.5/17	13.5/17	13.5/17	13.5/17	17.5/22	17.5/22	21/26.5
Piping connections	Liquid/gas pipe	mm	Φ6.35/Φ12.7	Φ6.35/Φ12.7	Φ6.35/Φ12.7	Φ6.35/Φ12.7	Φ6.35/Φ12.7	Φ9.53/Φ15.9	Φ9.53/Φ15.9
	Drain pipe	mm	OD Φ25	OD Φ25	OD Φ25	OD Φ25	OD Φ25	OD Φ25	OD Φ25
Standard controller			Wireless remote controller						