

Four-way Cassette (DC fan motors)

Model			MI-28Q4/DHN1-D	MI-36Q4/DHN1-D	MI-45Q4/DHN1-D	MI-56Q4/DHN1-D	MI-71Q4/DHN1-D
Power supply			1-phase,220-240V,50/60Hz				
Capacity	Cooling	kW	2.8	3.6	4.5	5.6	7.1
	Heating	kW	3.2	4.0	5.0	6.3	8.0
Power input	Cooling	W	25	25	31	31	46
	Heating	W	25	25	31	31	46
Airflow rate(H/M/L)		m ³ /h	982/832/677	982/832/677	1029/857/704	1029/857/704	1200/996/748
Sound pressure level(H/M/L)		dB(A)	42/37/32	42/37/32	43/38/34	43/38/34	45/39/34
Sound power level(H/M/L)		dB(A)	53/49/45	53/49/45	54/50/47	54/50/47	56/51/47
Main body	Net dim.(W×H×D)	mm	904×230×840	904×230×840	904×230×840	904×230×840	904×230×840
	Packing dim.(W×H×D)	mm	955×260×955	955×260×955	955×260×955	955×260×955	955×260×955
	Net/gross weight	kg	21.8/27.6	21.8/27.6	24/29.5	24/29.5	24/29.5
Panel	Net dim.(W×H×D)	mm	950×54.5×950	950×54.5×950	950×54.5×950	950×54.5×950	950×54.5×950
	Packing dim.(W×H×D)	mm	1035×90×1035	1035×90×1035	1035×90×1035	1035×90×1035	1035×90×1035
	Net/gross weight	kg	5/8	5/8	5/8	5/8	5/8
Piping connections	Liquid/gas pipe	mm	Φ6.35/Φ12.7	Φ6.35/Φ12.7	Φ6.35/Φ12.7	Φ9.53/Φ15.9	Φ9.53/Φ15.9
	Drain pipe	mm	OD Φ32	OD Φ32	OD Φ32	OD Φ32	OD Φ32
Standard controller			Wireless remote controller				