

Model			MKA-600F	MKA-750F	MKA-850F
Power supply		V/Ph/Hz	220-240/1/50		
Air flow (H/M/L)		m³/h	1150/800/690	1460/1020/880	1480/1040/890
		CFM	680/470/410	860/600/510	870/610/520
Cooling	Capacity (H/M/L)	kW	5.1/4.08/3.76	5.93/4.41/3.94	6.17/5.13/4.59
	Water flow rate	l/h	877	1020	1061
	Water pressure drop	kPa	15	17	20
Heating	Capacity (H/M/L)	kW	6.67/5.87/5.07	7.87/6.85/5.9	8.06/6.93/6.05
	Water flow rate	l/h	574	677	693
	Water pressure drop	kPa	37	41	39
Power input (H/M/L)		W	170/120/85	188/135/90	198/140/100
Sound pressure level (H/M/L)		dB(A)	42/32/26	44/34/28	46/36/30
Fan motor	Type	Low noise 3-speed fan motor			
	Quantity	1			
Fan	Type	Centrifugal, forward-curved Blades			
	Quantity	1			
Coil	Row	2			
	Max. working pressure	MPa	1.6		
	Diameter	mm	Ø7		
Panel	Net dimensions (W×H×D)	mm	950×45×950		
	Packing size (W×H×D)	mm	1035×90×1035		
	Net weight	kg	6		
	Gross weight	kg	9		
Body	Net dimensions (W×H×D)	mm	840×300×840		
	Packing size (W×H×D)	mm	900×307×900		
	Net weight	kg	35		
	Gross weight	kg	41		
Pipe connections	Water inlet/outlet pipe	Inch	Cold water: RC3/4; Hot water: RC1/2		
	Drain pipe	mm	ODØ32		

Model			MKA-950F	MKA-1200F	MKA-1500F
Power supply		V/Ph/Hz	220-240/1/50		
Air flow (H/M/L)		m³/h	1720/1200/1030	1860/1300/1110	2100/1470/1260
		CFM	1010/700/610	1090/760/650	1230/860/740
Cooling	Capacity (H/M/L)	kW	6.7/5.48/4.85	9.28/7.45/6.5	10.58/7.45/6.5
	Water flow rate	l/h	1152	1596	1820
	Water pressure drop	kPa	22	32	38
Heating	Capacity (H/M/L)	kW	8.67/7.63/6.59	11.65/10.49/8.85	12.62/11.36/9.47
	Water flow rate	l/h	746	1002	1085
	Water pressure drop	kPa	42	57	61
Power input (H/M/L)		W	205/145/105	197/135/103	234/165/115
Sound pressure level (H/M/L)		dB(A)	47/38/32	48/40/34	50/42/36
Fan motor	Type	Low noise 3-speed fan motor			
	Quantity	1			
Fan	Type	Centrifugal, forward-curved Blades			
	Quantity	1			
Coil	Row	2	3	3	
	Max. working pressure	MPa	1.6		
	Diameter	mm	Ø7		
Panel	Net dimensions (W×H×D)	mm	950×45×950		
	Packing size (W×H×D)	mm	1035×90×1035		
	Net weight	kg	6		
	Gross weight	kg	9		
Body	Net dimensions (W×H×D)	mm	840×300×840		
	Packing size (W×H×D)	mm	900×307×900		
	Net weight	kg	35	38	38
	Gross weight	kg	41	44	44
Pipe connections	Water inlet/outlet pipe	Inch	Cold water: RC3/4; Hot water: RC1/2		
	Drain pipe	mm	ODØ32		