



ENERG

енергия · ενέργεια



MHA-V8W/D2N1 SMK-80/CD30GN1-B



55°C

35



43dB



69dB

■ 7

■ 7

■ 7

kW

■ 8

■ 8

■ 8

kW



2015

811/2013

Technical parameters

Model(s):	Outdoor unit: MHA-V8W/D2N1 Indoor unit: SMK-80/CD30GN1-B
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	YES
Heat pump combination heater:	NO
Declared climate condition:	AVERAGE
Parameters are declared for medium-temperature application.	

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	7	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	6.1	kW
Tj = 2 °C	Pdh	3.8	kW
Tj = 7 °C	Pdh	2.5	kW
Tj = 12 °C	Pdh	2.2	kW
Tj = bivalent temperature	Pdh	6.1	kW
Tj = operating limit	Pdh	6.2	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	T _{biv}	-7	°C
Cycling interval capacity for heating	P _{cy ch}	-	kW
Degradation co-efficient (**)	C _{dh}	0.9	--
Power consumption in modes other than active mode			
Off mode	P _{off}	0.019	kW
Standby mode	P _{sb}	0.019	kW
Thermostat-off mode	P _{to}	0.051	kW
Crankcase heater mode	P _{ck}	0.014	kW

Other items			
Capacity control	variable		
Sound power level, indoors/ outdoors	L _{WA}	43/69	dB
Annual energy consumption	Q _{HE}	4474	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η _s	125	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COP _d	2.00	-
Tj = 2 °C	COP _d	3.06	-
Tj = 7 °C	COP _d	4.22	-
Tj = 12 °C	COP _d	6.52	-
Tj = bivalent temperature	COP _d	2.00	-
Tj = operating limit	COP _d	1.71	-
For air-to-water heat pumps: Tj = -15 °C	COP _d	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval efficiency	COP _{cy c}	-	-
Heating water operating limit temperature	W _{TOL}	60	°C
Supplementary heater			
Rated heat output (**)	P _{sup}	0.7	kW
Type of energy input	Electrical		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	5116	m ³ /h
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η _{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	GD Midea Heating & Ventilating Equipment Co. Ltd (Penglai industry road, Beijiao, Shunde, Foshan, Guangdong, P.R China)						

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Technical parameters

Model(s):	Outdoor unit: MHA-V8W/D2N1 Indoor unit: SMK-80/CD30GN1-B
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	YES
Heat pump combination heater:	NO
Declared climate condition:	COLDER

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	7	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _J			
T _J = -7 °C	P _d	4.5	kW
T _J = 2 °C	P _d	3.0	kW
T _J = 7 °C	P _d	2.4	kW
T _J = 12 °C	P _d	2.2	kW
T _J = bivalent temperature	P _d	5.3	kW
T _J = operating limit	P _d	4.3	kW
For air-to-water heat pumps: T _J = -15 °C	P _d	-	kW
Bivalent temperature	T _{biv}	-14	°C
Cycling interval capacity for heating	P _{cy}	-	kW
Degradation co-efficient (**)	C _{dh}	0.9	-
Power consumption in modes other than active mode			
Off mode	P _{off}	0.019	kW
Standby mode	P _{sb}	0.019	kW
Thermostat-off mode	P _{to}	0.051	kW
Crankcase heater mode	P _{ck}	0.014	kW

Other items			
Capacity control	variable		
Sound power level, indoors/ outdoors	L _{WA}	-	dB
Annual energy consumption	Q _{HE}	7319	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η _s	87	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _J			
T _J = -7 °C	COP _d	2.13	-
T _J = 2 °C	COP _d	3.16	-
T _J = 7 °C	COP _d	4.47	-
T _J = 12 °C	COP _d	6.49	-
T _J = bivalent temperature	COP _d	1.6	-
T _J = operating limit	COP _d	1.24	-
For air-to-water heat pumps: T _J = -15 °C	COP _d	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	-20	°C
Cycling interval efficiency	COP _{cy}	-	-
Heating water operating limit temperature	W _{TOL}	60	°C
Supplementary heater			
Rated heat output (**)	P _{sup}	2.0	kW
Type of energy input	Electrical		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	5116	m ³ /h
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h

For heat pump combination heater:

Declared load profile				Water heating energy efficiency			
Declared load profile	-			η _{wh}	-	%	
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ

Contact details: GD Midea Heating & Ventilating Equipment Co. Ltd (Penglai industry road, Beijiao, Shunde, Foshan, Guangdong, P.R China)

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(T_J).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Technical parameters

Model(s):	Outdoor unit: MHA-V8W/D2N1 Indoor unit: SMK-80/CD30GN1-B
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	YES
Heat pump combination heater:	NO
Declared climate condition:	WARMER
Parameters are declared for medium-temperature application.	

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	7	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	-	kW
Tj = 2 °C	Pdh	7.2	kW
Tj = 7 °C	Pdh	4.7	kW
Tj = 12 °C	Pdh	2.1	kW
Tj = bivalent temperature	Pdh	7.2	kW
Tj = operating limit	Pdh	7.2	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	T _{biv}	2	°C
Cycling interval capacity for heating	P _{cy ch}	-	kW
Degradation co-efficient (**)	C _{dh}	0.9	--
Power consumption in modes other than active mode			
Off mode	P _{off}	0.019	kW
Standby mode	P _{sb}	0.019	kW
Thermostat-off mode	P _{to}	0.051	kW
Crankcase heater mode	P _{ck}	0.014	kW

Other items			
Capacity control	variable		
Sound power level, indoors/ outdoors	L _{WA}	-	dB
Annual energy consumption	Q _{HE}	2572	kWh

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η _{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ

Contact details: GD Midea Heating & Ventilating Equipment Co. Ltd (Penglai industry road, Beijiao, Shunde, Foshan, Guangdong, P.R China)

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9.

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	ηs	149	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COPd	-	-
Tj = 2 °C	COPd	2.24	-
Tj = 7 °C	COPd	3.22	-
Tj = 12 °C	COPd	5.00	-
Tj = bivalent temperature	COPd	2.24	-
Tj = operating limit	COPd	2.24	-
For air-to-water heat pumps: Tj = -15 °C	COPd	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval efficiency	COP _{cy c}	-	-
Heating water operating limit temperature	W _{TOL}	60	°C
Supplementary heater			
Rated heat output (**)	Psup	0	kW
Type of energy input	Electrical		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	5116	m ³ /h
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h